

Features :

- 600A AC Current
- AC/DC V, AC A
- Continuity, Diode
- Data Hold, Auto Power OFF
- Jaw Diameter 28mm
- Backlight LCD Display



Technical Specifications :

Model	Metrix+ 125A+
LCD Display	1999 count, Backlight
Safety Standard	IEC 1010-1(EN 1010-1) pollution 2 Cat 600V UL-3111-1
Range	Manual
DC Voltage	600V $\pm(1.0\% + 3)$
AC Voltage	600V $\pm(1.5\% + 5)$
AC Ampere	2/20/200/600A $\pm(2.5\% \pm 8)$
Resistance	2k Ω /2000k Ω $\pm(1.2\% \pm 3)$
Input Impedance	$\geq 10M\Omega$
Jaw Diameter	28mm
Other Functionalities	Diode Test, On-Off Buzzer, Low Battery Display, Data Hold, Auto Power OFF, Function Protection
Storage Temperature & Humidity	-20°C ~ 60°C, $\leq 80\%RH$
Operating Temperature & Humidity	0°C ~ 40°C, $\leq 70\%RH$
Battery	AAA 1.5V x 2
LCD Size	24.3 x 34.6mm
Dimension & Weight	185x25x51mm, 160g
Accessories Included	Instruction Manual, Test Lead, Color Box, Battery