

Features :

- 1000A True RMS
- Inrush current
- Auto range
- AC/DC V, AC A
- Continuity, Diode
- Data Hold, Auto Power OFF
- Jaw Diameter 52mm
- Double Insulation protection class II
- Auto negative polarity indication “-“
- Low Battery indication
- Overload Protection.



Technical Specifications :

| Model | Metrix+ 2250T |
|----------------------------------|---|
| LCD Display | 3 3/4 Digit 3999 count |
| Safety Standard | IEC 61010-1 |
| Range | Auto Range |
| DC Voltage | 400mV/4/40/400/1000V, ±1%±3d |
| AC Voltage | 400mV/4/40/400/700V, ±1.5%±5d |
| AC Ampere | 4/40/400/1000A, ±2%±10d |
| Resistance | 400/4k/40k/400k/4mΩ, ±1%±3d 40mΩ, ±1.5%±5d |
| Capacitance | 10n/100n/1u/10u/100u/1m/10mF, ±3%±5d |
| Frequency | 100Hz/1k/10k/100k/1M/10M/40MHz, ±0.5%±3d |
| Duty | 1% ~ 99%, ±0.5%±3d |
| Temperature | -50°C ~ 300°C, ±1%±5d 301°C ~ 1000°C, ±1.9%±5d |
| Jaw Diameter | 52mm |
| Other Functionalities | Continuity, Diode, Data Hold, Auto Power OFF |
| Storage Temperature & Humidity | -20°C ~ 60°C, ≤80%RH |
| Operating Temperature & Humidity | 0°C ~ 40°C, ≤70%RH |
| Battery | 1.5V x 2 AA |
| Dimension & Weight | 249×89×38mm, 360g(including battery) |
| Accessories Included | Instruction Manual, Test Lead, Carry case, Battery & “K” Thermocouple |