

Features:

- 600A True RMS
- Auto & Manual range
- Continuity, diode, NCV
- Overload protection, data hold, auto power OFF
- Jaw Diameter 27mm
- Low Battery indication
- Backlight LCD Display



Technical Specifications:

Model	Metrix+ 225A+
LCD Display	3999 count, Backlight display
Range	Manual + Auto
DC Voltage	400m/4/40/400/600V $\pm(0.5\% \pm 5)$
AC Voltage	4/40/400/600V $\pm(1.2\% + 5)$
AC Ampere	4/40/400/600A $\pm(2\% + 10)$
Resistance	400/4k/40k/400k/4M Ω $\pm(1\% + 5)$ 40M Ω $\pm(1.5\% + 5)$
Capacitance	10n/100n/1u/10u/100u/1000uF $\pm(3\% + 5)$ 10mF $\pm(5\% + 5)$
Frequency	10/100/1k/10k/100k/1M/10M/40MHz $\pm(0.5\% + 3)$
Duty Ratio(ACV Test)	10 ~ 90% $\pm(0.5\% + 3)$
Temperature	-50°C ~ 300°C $\pm(1.2\% + 4)$ 301°C ~ 1000°C $\pm(1.9\% + 15)$
Jaw Diameter	27mm
Other Functionalities	Diode (LED), continuity buzzer, NCV, Low Battery indication, Data Hold, Auto Power OFF, overload protection
Battery	AAA 1.5V x 2
Dimension & Weight	213×80×35mm, 230g(with battery)
Accessories Included	Instruction Manual, Test Lead, Color Box, Battery