

#### Features :

- 600A True RMS
- Auto & Manual range
- AC/DC V, AC/DC A
- Continuity, Diode
- Data Hold, Auto Power OFF
- Jaw Diameter 28mm
- Low Battery indication
- Backlight LCD Display



#### Technical Specifications :

Model	Metrix+ 725A+
LCD Display	5999 count, Backlight Display , 24.3 x 34.6mm
Safety Standard	GB/T 13978-92 GB-4793.1-1995 IEC -61010-1 IEC 61010-2-032 Pollution 2 Cat II 600V
Range	Manual + Auto
DC Voltage	6/60V $\pm(0.8\% + 5)$ 600V $\pm(1.0\% + 5)$
AC Voltage	6/60V $\pm(1.2\% + 5)$ 600V $\pm(1.5\% + 5)$
DC Ampere	60/600A $\pm(2.0\% + 10)$
AC Ampere	60/600A $\pm(2.5\% + 8)$
Resistance	600/6k/60k/600k $\pm(0.8\% + 3)$ 6M/60M $\Omega$ $\pm(1.2\% + 3)$
Capacitance	9.999n/99.99n/999.9nF $\pm(3.0\% + 5)$ 9.999u/99.99u/999.9uF $\pm(3.0\% + 5)$ 9.999m/99.99mF $\pm(5.0\% + 5)$
Frequency(ACV Test)	10kHz ~ 100kHz $\pm(0.3\% + 5)$
Duty Ratio(ACV Test)	10 ~ 90% $\pm(0.5\% + 3)$
Temperature	-50°C ~ 300°C $\pm(1.0\% + 4)$ 301°C ~ 1000°C $\pm(1.9\% + 5)$
Jaw Diameter	28mm
Input Impedance	$\geq 10M\Omega$
Other Functionalities	Diode, On-Off Buzzer, Low Battery Display, Data Hold, Auto Power OFF, Function Protection
Battery	AAA 1.5V x 2
Dimension & Weight	185×25×51mm, 160g
Accessories Included	Instruction Manual, Test Lead, Color Box, Battery