


Reference Gages

Radius Gages
SERIES 186

- Radius size is stamped on each gage leaf.
- Each leaf comprises an internal and an external radius gage of the same size.
- With locking clamp.




SPECIFICATIONS

Metric				
Code No.	Range (mm)	Accuracy	Composition of leaves	Remarks
186-110	0.4 - 6	±0.04 mm	18 leaves: 0.4, 0.8, 1, 1.2, 1.5, 1.6 mm, 1.75 - 3 mm by 0.25 mm, 3.5 - 6 mm by 0.5 mm	90° arc
186-902	0.5 - 13		26 leaves: 0.5 - 13 mm by 0.5 mm	90° arc, separate part type
186-105	1 - 7		34 leaves: 1 - 3 mm by 0.25 mm, 3.5 - 7 mm by 0.5 mm	180° arc
186-106	7.5 - 15		32 leaves: 7.5 - 15 mm by 0.5 mm	180° arc
186-107	15.5 - 25		30 leaves: 15.5 - 20 mm by 0.5 mm, 21 - 25 mm by 1 mm	180° arc

Inch				
Code No.	Range (in)	Accuracy	Composition of leaves	Remarks
186-103	1/32 - 17/64	±0.002 in	16 leaves: 1/32 in - 17/64 in by 64ths	90° arc
186-101	1/32 - 1/4		30 leaves: 1/32 in - 1/4 in by 64ths	180° arc
186-102	17/64 - 1/2		32 leaves: 17/64 in - 1/2 in by 64ths	180° arc
186-104	9/32 - 33/64		16 leaves: 9/32 in - 33/64 in by 64ths	90° arc
186-901*	1/64 - 1/2		25 leaves: 1/64 in - 17/64 in by 64ths, 9/32 in - 1/2 in by 32nds	Holder
186-903	1/64 - 17/64	±0.0016 in	17 leaves: 1/64 in - 17/64 in by 64ths	—
186-904	9/32 - 1/2		8 leaves: 9/32 in - 1/2 in by 32nds	—
186-905	9/16 - 1		8 leaves: 9/16 in - 1 in by 16ths	Holder
186-906	0.010 - 0.500		26 leaves: 0.10 in - 0.30 in by 0.005 in 0.40 in - 0.100 in by 0.010 in 0.120 in - 0.300 in by 0.020 in 0.350 in - 0.500 in by 0.050 in	Holder
186-907	0.550 - 1		10 leaves: 0.550 in - 1 in by 0.50 in	—


* Each gage has five measuring locations.



Composition of leaves for 186-902

Thread Pitch Gages
SERIES 188

- Thread pitch is stamped on each gage.
- Metric, Unified, and Whitworth screw pitch gages.



SPECIFICATIONS

Metric Screw Pitch Gages

Code No.	Range (mm)	Integration pitch error	Composition of leaves
188-130	0.35 - 6	±0.05 mm	22 leaves: 0.35, 0.4, 0.45, 0.5, 0.6, 0.7, 0.75, 0.8, 1, 1.25, 1.5, 1.75, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6 mm and 60° angle gage
188-122	0.4 - 7		21 leaves: 0.4, 0.5, 0.7, 0.75, 0.8, 0.9, 1, 1.25, 1.5, 1.75, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7 mm
188-121	0.4 - 7		18 leaves: 0.4, 0.5, 0.75, 1, 1.25, 1.5, 1.75, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7 mm

Unified Screw Pitch Gages

Code No.	Range	Integration pitch error	Composition of leaves
188-111	4 - 42 TPI	±0.002 in	30 leaves: 4, 4 ^{1/2} , 5, 5 ^{1/2} , 6, 7, 8, 9, 10, 11, 11 ^{1/2} , 12, 13, 14, 15, 16, 18, 20, 22, 24, 26, 27, 28, 30, 32, 34, 36, 38, 40, 42 TPI

Note: Metric and Unified Pitch Gage Set (188-151) is available.

Metric and Unified Screw Pitch Gage Set

Code No.	Range	Integration pitch error	Composition of leaves
188-151	0.4 - 7 mm/4 - 42 TPI	±0.05 mm/ ±0.002 in	51 leaves: Set of 188-122 and 188-111

Whitworth Screw Pitch Gages

Code No.	Range	Integration pitch error	Composition of leaves
188-101	4 - 42 TPI	±0.002 in	30 leaves: 4, 4 ^{1/2} , 5, 5 ^{1/2} , 6, 7, 8, 9, 10, 11, 11 ^{1/2} , 12, 13, 14, 15, 16, 18, 20, 22, 24, 26, 27, 28, 30, 32, 34, 36, 38, 40, 42 TPI
188-102	4 - 60 TPI		28 leaves: 4, 4 ^{1/2} , 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32, 34, 36, 40, 48, 60 TPI