

This is a moisture tester of DC resistance(built-in probe type), widely applied in the fields of testing the moisture content in the woods, bamboo ware, paper articles and those materials of wood fibre construction.

### Features:

- Selection among 4 types of wood species.
- Reading lock.
- Auto temperature compensation for varying environment.
- Review of maximum moisture reading
- Battery volume alert
- Display on environment temperature and humidity
- Large non-parallax LCD with legible display
- Automatic/manual power off.



### Wood type and other material :

**Wood Type 1 :** Rhodesia teak, Ormosia, Brazil walnut.

**Wood Type 2 :** Walnut tree, White poplar, Teak.

**Wood Type 3:** Banyan pine, Douglas fir, Lauan, Manchurian ash, European silver, Maple, White ash, African whitewood, Rose wood, Elm tree, Gmelina chinensis benth, Hemlock, Dipterocarpus, Oak.

**Wood Type 4 :** Chinese red pine, Coquito, Abies holophylla maxim, Larch, Apiton, Birch, Basswood.

### Technical Specifications :

Model	Metrix+ MM 2A+
Measuring range	Type 1 : 2 ~ 40%; Type 2 : 2 ~ 50% Type 3 : 2 ~ 60% Type 4 : 2 ~ 70%
Precision	±1% + 0.5
Resolution	0.5%
Temperature	-10 ~ 60°C; ±1°C; 0.1°C
Humidity	20 ~ 95% RH; ±5% RH; 0.1% RH
Operating temperature	0°C-40°C
Operating humidity	20% ~ 95%RH
Automatic power off time	About 10 minute
Length of probe	9.8mm
Battery	2*1.5V AAA Battery
Size	135.6*55*29.4mm
Weight	107.7g(excluding battery)
Packing	Gift box Packing
Standard Accessories	Main unit, Manual